

SCR331

Contact Smart Card Reader



Features

- Ergonomic and cost efficient design
- Software and functionality compatible with SCM's SCR33xx readers family
- In field upgradable
- EMV Level 1 certified
- Compliant with all major smart cards and relevant industry standards
- Customization options: Casing color and company logo OEM branding

Typical Applications

The SCR331 is suitable for a wide range of applications for government as well as for enterprise and home usage.

Due to its design, the reader is also ideally suited to be bundled with smart cards and software to support large scale projects roll outs.

Typical applications areas of the SCR331 are electronic ID, social security and loyalty programs, e-Coupons, secure network log on, e-Banking as well as online shopping and gaming activities.

Contact Reader

U.S. Headquarters
SCM Microsystems Inc.
1900-B Carnegie Avenue
Santa Ana, CA 92705 USA
E-mail scmsales@scmmicro.com
Phone +1 510 360 2300
Fax +1 510 360 0211

European Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
85737 Ismaning, Germany
E-mail sales@scmmicro.de
Phone +49 89 9595 5000
Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
GoogolPlex Millennium Building 6F
4-4-20 Shiba, Minato-ku,
Tokyo, Japan 108-0014
E-mail sales@scmmicro.co.jp
Phone +81 3 6414 6611
Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd.
Module No. 0506, 0507 & 0508
D' Block South, 5th Floor
Tidel Park, 4 Canal Bank Road
Taramani
Chennai 600113, India
E-mail sales@scmmicro.co.in
Phone +91 44 2254 0020
Fax +91 44 2254 0029

www.scmmicro.com

SCR331

Technical Data

Interfaces		
Host	USB	<ul style="list-style-type: none"> • Full speed USB 2.0 (12 Mbps) • USB Bus powered device • CCID compliant
Smart Card	contact	<ul style="list-style-type: none"> • T=0, T=1 protocol support • Memory card support through SCM MCARD API • Communication speed up to 344,105 bps (PPS, FI parameter) • Frequency up to 8 MHz (PPS, DI parameter) • Support ISO 7816 Class A and AB smart card • 8 contacts - ISO location • 100,000 insertions • Sliding contact
Human	optical	<ul style="list-style-type: none"> • One green LED
Software	API	<ul style="list-style-type: none"> • PC/SC • CT-API (thru wrapper on top of PC/SC)
Operating Systems		<ul style="list-style-type: none"> • Windows® 7 • Windows® Vista, XP, Server 2003, 2000, ME, 98 • Windows® Vista, XP, Server2003 (AMD64/EMT64) • Windows® CE 3.0, 4.1, 4.2, 5.0, 6.0 • MacOS, Solaris, Linux 32-bit (2.4.x, 2.6.x)/64-bit
Cable		<ul style="list-style-type: none"> • Cable: 1.5m long with USB type A connector
Dimensions	L x W x H [mm]	• 90 x 70 x 16.5
Weight	[g]	• 100
Operating Conditions	Temperature [°C] Humidity [%]	<ul style="list-style-type: none"> • 0 to 50 • 90 (non-condensing)
Approvals	Functional	<ul style="list-style-type: none"> • FCC Class B part 15, cULus, CE, VCCI, ANZI, CNS • USB-IF • Microsoft® WHQL 2000, XP, Server 2003 • EMV Level 1
	Environmental	• RoHS, WEEE

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- Innovative solutions - more than 50 patents filed
- Reliable high-quality mass production capability - more than 15 Mio. reader solutions deployed to date
- Active role in standardization committees
- Complex project management expertise e.g. U.S. Department of Defense CAC program, electronic ID applications (ePassport, health card projects, national ID, driver licence)

Support

- Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

Trusted Products

- Broadest portfolio of security technology products - for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design - certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions - SCM's SmartOS™ firmware and its own ASIC technology allow in Field upgrades and secure your investment

