

# SCR3340

## ExpressCard54™ Contact Smart Card Reader



### Features

- ISO7816 contact card reader
- Robust metal casing with open-end mouth for convenient smart card insertion/removal
- USB2.0 full-speed interface and standard USB2.0 driver architecture
- Smaller and lighter than a PCMCIA card reader
- In field firmware updates
- Compliant with all major smart cards and relevant industry standards
- Customization options: Company logo OEM branding on the label

### Typical Applications

The SCR3340 is available for built-in integration into notebooks, PDAs, Thin-Client systems and into Express Card54™ Adapters for PC systems. It is suitable for a wide range of applications, e.g. home banking, network security, secure logon, email encryption, online gaming, as well as online loyalty points redemption and other PC related applications.

Its robust metal casing ensures highest durability in all conditions.

### Contact Reader

U.S. Headquarters  
SCM Microsystems Inc.  
41740 Christy Street  
Fremont, CA 94538 USA  
E-mail [scmsales@scmmicro.com](mailto:scmsales@scmmicro.com)  
Phone +1 510 360 2300  
Fax +1 510 360 0211

European Headquarters  
SCM Microsystems GmbH  
Oskar-Messter-Str. 13  
85737 Ismaning, Germany  
E-mail [sales@scmmicro.de](mailto:sales@scmmicro.de)  
Phone +49 89 9595 5000  
Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.  
GoogolPlex Millennium Building 6F  
4-4-20 Shiba, Minato-ku,  
Tokyo, Japan 108-0014  
E-mail [sales@scmmicro.co.jp](mailto:sales@scmmicro.co.jp)  
Phone +81 3 6414 6611  
Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd.  
Module No. 0506, 0507 & 0508  
D' Block South, 5th Floor  
Tidel Park, 4 Canal Bank Road  
Taramani  
Chennai 600113, India  
E-mail [sales@scmmicro.co.in](mailto:sales@scmmicro.co.in)  
Phone +91 44 2254 0020  
Fax +91 44 2254 0029

[www.scmmicro.com](http://www.scmmicro.com)

# SCR3340

## Technical Data

Interfaces						
Host	USB	<ul style="list-style-type: none"> <li>ExpressCard 54</li> <li>Full speed USB 2.0 (12 Mbps)</li> <li>USB Bus powered device</li> <li>CCID compliant</li> </ul>				
Smart Card	contact	<ul style="list-style-type: none"> <li>T=0, T=1 protocol support</li> <li>Memory card support through SCM MCard API</li> <li>Communication speed up to 344,105 bps (DI)</li> <li>Frequency up to 8 MHz (FI)</li> <li>Support ISO 7816 Class A and AB smart card</li> <li>8 contacts - ISO location</li> <li>50,000 insertion/removal cycle</li> <li>Friction contact</li> </ul>				
Software	API	<ul style="list-style-type: none"> <li>PC/SC</li> <li>CT-API (thru wrapper on top of PC/SC)</li> </ul>				
Operating Systems		<ul style="list-style-type: none"> <li>Windows® Vista, XP, Server2003, 2000, ME, 98</li> <li>Windows® Vista, XP, Server2003 (AMD64/EMT64)</li> <li>Windows® CE 3.0, 4.1, 4.2, 5.0, 6.0</li> <li>MacOS X</li> <li>Linux 32-bit (2.4.x, 2.6.x) / 64-bit</li> </ul>				
Connector		<ul style="list-style-type: none"> <li>26 pins ExpressCard edge connector</li> </ul>				
Dimensions		L x W x H [mm] <ul style="list-style-type: none"> <li>75 x 54 x 5 (ExpressCard 54 )</li> </ul>				
Weight		[g] <ul style="list-style-type: none"> <li>25</li> </ul>				
Operating Conditions		Temperature [°C] <ul style="list-style-type: none"> <li>0 to 50</li> </ul> Humidity [%] <ul style="list-style-type: none"> <li>90 (non-condensing)</li> </ul>				
Reliability/MTBF		<ul style="list-style-type: none"> <li>&gt; 100,000 hrs as per MIL-HDBK-217F</li> </ul>				
Approvals		<table border="0"> <tr> <td>Functional</td> <td> <ul style="list-style-type: none"> <li>FCC Class B part 15, UL, CE</li> <li>USB-IF</li> <li>Microsoft® WHQL 2000, XP, Server2003</li> <li>ExpressCard</li> <li>EMV 2000 Level 1</li> </ul> </td> </tr> <tr> <td>Environmental</td> <td> <ul style="list-style-type: none"> <li>RoHS, WEEE</li> </ul> </td> </tr> </table>	Functional	<ul style="list-style-type: none"> <li>FCC Class B part 15, UL, CE</li> <li>USB-IF</li> <li>Microsoft® WHQL 2000, XP, Server2003</li> <li>ExpressCard</li> <li>EMV 2000 Level 1</li> </ul>	Environmental	<ul style="list-style-type: none"> <li>RoHS, WEEE</li> </ul>
Functional	<ul style="list-style-type: none"> <li>FCC Class B part 15, UL, CE</li> <li>USB-IF</li> <li>Microsoft® WHQL 2000, XP, Server2003</li> <li>ExpressCard</li> <li>EMV 2000 Level 1</li> </ul>					
Environmental	<ul style="list-style-type: none"> <li>RoHS, WEEE</li> </ul>					

Technical data are subject to change without notice.

## The SCM Microsystems' Advantage

### Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- Innovative solutions - more than 50 patents filed
- Reliable high-quality mass production capability - more than 15 Mio. reader solutions deployed to date
- Active role in standardization committees
- Complex project management expertise e.g. U.S. Department of Defense CAC program, electronic ID applications (ePassport, health card projects, national ID, driver licence)

### Support

- Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

### Trusted Products

- Broadest portfolio of security technology products - for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design - certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions - SCM's SmartOS™ firmware and its own ASIC technology allow in Field upgrades and secure your investment

